Statement of Work (SOW)

for the

Inspect and Repair Only As Necessary (IROAN)

of the

Mine Clearance Launcher MK 154

NSN 1055-01-226-6338

B1315

TABLE OF CONTENTS

SECTION/PARAGE 1.0 SCOPE	<u>RAPH</u>	<u>PAGE</u>	1
			1
1.1 Background	DOCLIMENTS		
2.0 APPLICABLE			1
2.1 Military Specifi			1
2.2 Military Standa	rds		1
2.3 Other Governme	ent Documents and Publications		2
2.4 Industry Standar	rds		3
3.0 REQUIREMEN	NTS		3
3.1 General Tasks			3
3.2 Detail Tasks			3
3.2.1 Phase I - Pre-	Induction		4
3.2.2 Phase II - IRC	DAN		4
3.2.3 Phase III - Ins	pection, Testing and Acceptance		5
3.2.4 Phase IV - Packaging, Handling, Storage and Transportation (PHS&T)			6
3.3 Configuration N	Management		6
3.3.1 Configuration	Status Accounting (CSA)		6
3.3.2 Configuration	Control		7
3.4 Quality Assurar	nce Provisions		7
3.5 Acceptance			7
3.6 Rejection			7
3.7 Government Fu	rnished Equipment (GFE)/Government Furnished Materiel		7
(GFM)			
3.8 Contractor Furn	nished Materiel (CFM)		8
3.9 Pre-Induction C	Checklist		8
Appendix A	Pre-Induction Inspection Checklist		A-1
Appendix B	List of Defective Parts and Assemblies		B-1
Appendix C	List of Repair Parts and Assemblies Required for Repairs		C-1

Statement of Work (SOW) for the Inspect and Repair Only As Necessary (IROAN) of the Mine Clearance Launcher MK 154 NSN 1055-01-226-6338

- 1.0 <u>SCOPE</u>. This Statement of Work (SOW) establishes, sets forth tasks and identifies the work efforts that shall be performed by the Contractor in the IROAN effort of the Mine Clearance Launcher MK 154, hereafter referred to as the MK 154. This document contains requirements to restore the MK 154 to Condition Code "A". Condition Code "A" is defined as "serviceable/ issuable without qualification, new, used, repaired or reconditioned materiel which is serviceable and issuable to all customers without limitation or restriction, including materiel with more than six months shelf-life remaining". National Stock Number (NSN) 1055-01-226-6338 shall be known as the MK 154.
- 1.1 <u>Background</u>. IROAN is defined as "that maintenance technique which determines the minimum repairs necessary to restore equipment components or assemblies to prescribed maintenance serviceability standards by utilizing all available diagnostic equipment and test procedures in order to minimize disassembly and parts replacement".
- 2.0 <u>APPLICABLE DOCUMENTS</u>. The following documents form a part of this SOW to the extent specified. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto which is in effect on the date of solicitation. In the event of conflict between the documents referenced herein and the contents of this SOW, the contents of this SOW shall be the superseding requirement.

2.1 Military Specifications

MIL-C-46168	Coating, Aliphatic Polyurethane, Chemical Agent Resistant
MIL-C-53039	Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant
2.2 Military Standards	
MIL-STD-129	DoD Standard Practice: Military Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-461	Requirements for the Control of Electromagnetic Interference Emission and Susceptibility

MIL-STD-3003 Vehicles, Wheeled: Preparation for Shipment and

Storage of

2.3 Other Government Documents And Publications

DoD 4000.25-1-M	Military Standard Requisitioning and Issue Procedures (MILSTRIP)
DoD 4160.21-M-1	Defense Demilitarization Manual
DoD 4160.21-M	Defense Materiel Disposition Manual
SL-3-09962A	Launcher, Mine Clearance MK 154 Mod 0
TM 09962A-13&P/2	Mark 1 Mod 0 Mine Clearance System
MI-09962A-20/1	Elevation Cylinder Sleeve Stabilization
TI-09962A-35/1	Fabrication and Installation of Electrical Connector Guard for the Launcher, Mine Clearance MK 154
TM 3080-12	Corrosion Prevention and Control for Marine Corps Equipment
TM 3080-50	Corrosion Control Procedures Depot Maintenance Activities for Marine Corps Equipment
TM 4700-15/1H	Ground Equipment Record Procedures
TM 4750-15/1	Painting and Registration Marking for Marine Corps Combat and Tactical Equipment
TM 4750-15/2	Camouflage Paint Patterns
Engineering Drawing 835028A0000 CAGE 01365	Mine Clearance Launcher, MK154, Marine Corps
Engineering Drawing 835028B0000 CAGE 01365	Container Assembly for MK 154 Marine Corps
Reversed Engineering Drawing 835028C0000 CAGE 01365	Mine Clearance Launcher, MK154, Marine Corps

Military Handbooks (For Guidance)

MIL-HDBK-61

Configuration Management Guidance

2.4 Industry Standards

ANSI/ISO/ASQC Q9001-2000

Quality Management Systems - Requirements

Industry Standards (For Guidance)

ANSI/EIA-649

National Consensus Standard for Configuration

Management

Copies of Military Standards and Specifications are available from the DoD Single Stock Point, Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, commercial telephone number (215) 697-2179 or DSN 442-2179, or on the Internet at http://www.dodssp.daps.mil. Copies of other government documents and publications required by contractors in connection with specific SOW requirements shall be obtained through the Contracting Officer: Contracts Department (Code 891), P. O. Drawer 43019, 814 Radford Blvd., Marine Corps Logistics Command, Albany, Georgia 31704-3019, commercial telephone number (229) 639-6753 or DSN 567-6753. Copies of engineering drawings, if applicable, may be obtained by contacting Supply Chain Management Center, Attn: Code 566-1A, 814 Radford Blvd., STE 20320, Albany, Georgia 31704-0320, commercial telephone number (229) 639-6761 or DSN 567-6761.

3.0 REQUIREMENTS

- 3.1 General Tasks. In fulfilling the specified requirements, the Contractor shall:
- a. Provide materials, labor, facilities, missing parts, and repair parts necessary to inspect, diagnose, restore, and test the MK 154. Upon completion of IROAN, repaired equipment shall be Condition Code "A".
- b. Provide all tools and test equipment required to test, inspect, repair, and calibrate the MK 154.
- c. Conduct in process and final on-site testing for witness by Marine Corps Systems Command (MCSC), Code PMM152, Albany, Georgia representatives.
- d. Be responsible for all structural, electrical and mechanical requirements associated with the restoration of the MK 154.
- 3.2 Detail Tasks. The following tasks describe the different phases for IROAN of the MK 154.

- 3.2.1 Phase I Pre-Induction. The Contractor shall perform a Pre-Induction Inspection Analysis for each MK 154 using the Contractor's diagnosis, inspection and testing techniques to determine extent of work and parts required. This inspection shall include all items associated with the MK 154 as found in SL-3-09962A, TM 09962A-13&P/2, and TI-09962A-35/1. These findings shall be annotated on a Pre-Induction Check List (Appendix A) and shall be provided to the government in accordance with Paragraph 4.0 of this SOW.
- 3.2.2 Phase II IROAN. After Pre-Induction Tests and Inspections have been completed, repair of the MK 154 shall be accomplished by the Contractor in accordance with this SOW. Deficiencies noted on the Pre-Induction Checklist (Appendix A) during Phase I shall be repaired/replaced. The Contractor shall use the List of Defective Parts and Assemblies (Appendix B) to list all defective parts and assemblies. The Contractor shall also use the List of Repair Parts and Assemblies Required for Repairs (Appendix C) to report the parts used on the repaired MK 154. Components or assemblies shall not be disassembled for replacement of mandatory parts unless that part has failed, or the component assembly wherein the part is located is disassembled for repair.
- a. Pre-Induction Inspection Checklist Information recorded on the Pre-Induction Inspection Checklist (Appendix A) shall be used as a guide to repair the MK 154 system in accordance with this SOW.
- b. Technical Instruction (TI) All TI's not previously applied to the MK 154 shall be applied during the IROAN and shall be annotated on Equipment Record Jacket in accordance with TM 4700-15/1H.
 - c. Corrosion For corrosion prevention and treatment use TM 3080-12 and TM 3080-50.
 - d. Fluid Leaks The following shall be used as a guide in determining degree of fluid loss:
- (1) Class I Seepage of fluid (as indicated by wetness or discoloration) not great enough to form drops.
- (2) Class II Leakage of fluid great enough to form drops, but not enough to cause drops to fall from the item being checked/inspected.
- (3) Class III Leakage of fluid great enough to form drops that fall from the item being checked/inspected.

NOTE: A Class I leak, except in fuel or brake systems, is an acceptable condition at any time and does not require corrective action.

- e. Belts Replace all.
- f. Data Plates All required data plates and decals shall be in place and shall be legible. Each repaired MK 154 shall have an IROAN data plate affixed to the main unit in close

proximity to the existing data plate. The data plate shall meet the requirements of MIL-STD-130 and TM 4750-15/1 and shall contain the Equipment Serial Number, date of IROAN, date of SOW, SOW number, and company name of Contractor completing work.

- g. Painting/Coating (Exterior/Interior) If painting/coating is required, the MK 154 shall be cleaned in accordance with TM 3080-50, Chapter 4, and coated with Aliphatic Polyurethane Coating, in accordance with MIL-C-46168 or MIL-C-53039 using TM 4750-15/2 as pattern guidance if required.
- h. Demilitarization All end items that are identified as non-repairable and require demilitarization codes shall be reported to the MCSC, Code PMM152, Albany, Georgia representatives, who will provide disposition instructions in accordance with DoD 4160.21-M. and DoD 4160.21-M-1.
- i. Electromagnetic Emission All requirements pertaining to control of electromagnetic interference, emission and susceptibility shall be in accordance with MIL-STD-461.

j. Hardware.

- (1) Replace broken, unserviceable and/or missing hardware including nuts, bolts, screws, washers, turnlock fasteners, mandatory, safety and one-time use items, in accordance with TM 09962A-13&P/2. Unserviceable would include any of the above that failed to function properly.
- (2) Ensure proper hardware locking devices are present and operational on all moving mechanical assemblies.
- (3) Hardware normally supplied with commercial parts shall be used unless specifically prohibited.
- k. Hoses All hoses and fittings shall be visually inspected for damage or deterioration. Any hose showing signs of leakage, kinking or separation of outer coating shall be replaced. This inspection shall be performed during the Operational Test Inspection (OTI) of the MK 154.
- 1. Cable Assemblies All cables and cable connections shall be tested and visually inspected for damage or corrosion. Any cable or cable connector showing signs of damage, corrosion or separation of outer coating shall be repaired/replaced and tested with its respective component/assembly to assure satisfactory compliance with all operational tests.
 - m. Filters Replace all.

3.2.3 Phase III - Inspection, Testing and Acceptance

a. The Contractor shall conduct Inspection, Testing and Acceptance of the MK 154 in accordance with TM 09962A-13&P/2.

- b. The Contractor shall be responsible for conducting required tests and shall ensure representatives from MCSC, Code PMM152, Albany, Georgia and Contractor maintenance personnel are available to complete the final acceptance. Acceptance tests shall be held at the Contractor facility. MCSC, Code PMM152, Albany, Georgia representatives shall be given a minimum of two weeks notice prior to beginning acceptance testing. The test area shall be cleared of all equipment parts, components, not required for the test.
- c. The Contractor shall be responsible for correcting any deficiencies identified during inspection/testing. MCSC, Code PMM152, Albany, Georgia representatives may require the Contractor to repeat tests, or portions thereof, if the original tests fail to demonstrate compliance with this SOW.
- d. Acceptance Testing/Operational Tests on all MK 154 repaired under the provisions of this SOW shall be accomplished, by the Contractor, in accordance with TM 09962A-13&P/2. Operational Tests are to be conducted on each MK 154 upon completion of repairs and prior to the equipment being returned to stock to insure the unit will perform as required.

3.2.4 Phase IV - Packaging, Handling, Storage and Transportation (PHS&T)

- a. The Contractor shall be responsible for preservation and packaging of item(s) being repaired under the terms of this SOW. Items scheduled for long-term storage or shipment to overseas destinations shall be in accordance with Level "A" requirements of MIL-STD-3003. Items scheduled for domestic shipment for immediate use or short-term storage shall be to Level "B" requirement.
 - b. Marking for shipment and storage shall be in accordance with MIL-STD-129.
- c. The Marine Corps will provide the Contractor with the shipping address(es) for delivery of the repaired equipment. The Contractor shall be responsible for arranging for shipment to the pre-designated site(s). The Marine Corps will be responsible for transportation costs associated with shipping the subject equipment to and from the Contractor.

3.3 Configuration Management

3.3.1 Configuration Status Accounting (CSA)

- a. The Contractor shall record and submit data on retrofit accomplished during Phase II. Any approved Modifications Instructions (MIs) or Engineering Change Proposals (ECPs) not previously applied shall be incorporated during Phase II of the IROAN process.
- b. The Contractor shall determine the application status of approved configuration changes by visual inspections to the extent possible. The government will identify the configuration changes to be inspected by furnishing a Configuration Inspection Checklist to the Contractor. The Contractor shall use one checklist per MK 154 to record the inspection findings along with other required data.

- c. The Contractor shall record serial numbers of the assemblies listed on the Configuration Inspection Checklist. The Contractor shall also record the information on the Equipment Record Jacket in accordance with TM 4700-15/1H.
- 3.3.2 <u>Configuration Control</u>. The Contractor shall apply configuration control procedures to established configuration items. The baseline configuration for the MK 154 has been established by Engineer Drawing numbers 835028A0000, CAGE 01365, for the Mine Clearance Launcher, and 835028B0000, CAGE 01365, for the container and applicable MIs and ECPs. The contractor shall not implement configuration changes to an item's documented performance or design characteristics without prior written authorization. If it is necessary to temporarily depart from the authorized configuration, the contractor shall prepare and submit a Request for Deviation. MIL-HDBK-61 and ANSI/EIA-649 provide guidance for preparing this configuration control document.
- 3.4 <u>Quality Assurance Provisions</u>. The Contractor shall provide and maintain a Quality System that, as minimum, adheres to the requirements of ANSI/ISO/ASQC Q9001-2000 Quality Management Systems Requirements.
- 3.5 <u>Acceptance</u>. The performance of the Contractor and the quality of work delivered, including all equipment furnished and documentation written or compiled, shall be subject to in-process review and inspection during performance. Inspection may be accomplished in-plant or at any work site or location, and MCSC, Code PMM152, Albany, Georgia representatives shall be permitted to observe the work or to conduct inspection during normal Contractor's working hours. Final Inspection and Acceptance Testing shall be conducted at the Contractor Facility. Final acceptance shall be conducted on 100 percent of items to verify that the units meet all requirements.
- 3.6 <u>Rejection</u>. Failure to comply with any of the specified requirements listed herein shall be reason for rejection by MCSC, PMM152, Albany, Georgia. The Contractor shall, at no additional cost to MCSC, PMM152, Albany, Georgia, provide the following:
 - a. Develop an approach for modification or correction of all deficiencies.
- b. Upon approval of a documented approach, the Contractor shall correct the deficiencies and repeat the verification until an acceptable compliance with acceptance test procedures is demonstrated.
- 3.7 Government Furnished Equipment (GFE)/Government Furnished Materiel (GFM). The Management Control Activity (MCA) (Code 581-1B) will coordinate GFE/GFM requests and maintain a central control system on all government owned assets in the Contractor's possession. The MCA will forward a GFE Accountability Agreement to the Contractor for signature on an annual basis to establish a chain of custody and identify property responsibilities for Marine Corps assets. The Contractor is to acknowledge receipt of GFM to the MCA within 15 days of receipt. This can be done by mailing a copy of the DD 1348 to Materiel and Distribution Management Department, Distribution Management Branch, Management Control Activity

(Code 581-1B), 814 Radford Blvd, STE 20320, Albany, Georgia 31704-0320, or faxing a copy to commercial telephone number (229) 639-5498 or DSN 567-5498. If Depot Source of Repair (DSOR) mandated, assets at repair facility will not be considered GFE/GFM.

- 3.8 <u>Contractor Furnished Materiel (CFM)</u>. The Contractor may requisition materiel as required in the performance of the SOW through the DoD Supply System. DoD 4000.25-1-M (MILSTRIP), Chapter 11, provides guidance to Contractors on the requisitioning process. The Contractor's decision to utilize CFM procured from the DoD Supply System shall be based upon cost effectiveness, availability of materiel and the required completion/delivery date.
- 3.9 <u>Pre-Induction Checklist</u>. The Contractor shall complete the Pre-Induction Inspection Checklist (Appendix A), List of Defective Parts and Assemblies (Appendix B), and List of Repair Parts and Assemblies Required for Repairs (Appendix C), for each MK 154 repaired. These documents shall be available during final acceptance testing. One copy of each document shall be provided to Commanding General, Marine Corps Systems Command, Code PMM152, 814 Radford Blvd., STE 20343, Albany, Georgia 31704-0343, 30 days after final acceptance of each MK 154 in PDF Format Media.

The inspection checklist shall contain, but not be limited to the following:

- (1) MK 154 serial number. Appendix A, B, and C.
- (2) Condition Code of MK 154 at receipt. Appendix A.
- (3) Results of operational test. Appendix A.
- (4) List of defective parts and assemblies. Appendix B.
- (5) List of repair parts and assemblies required for repairs. Appendix C.
- (6) Corrosion prevention methods that shall be used will be documented on the first page of Appendix A.

Pre-Induction Inspection Checklist APPENDIX A

MK154 Serial number:	Condition Code at receipt:
Corrosion prevention methods that shall be use	d.
	VALUE - VALUE
APPLICATION OF THE PROPERTY OF	·

Inspect all components for operating/malfunction/defective parts per TM 09962A-13&P/2. Visually check components for leaks, damage, loose parts & hardware. No disassembly of components is allowed unless the component is determined to be defective.

Checklist APPENDIX A

COMPONENT	PASS	FAIL	REMARKS:
Mast Assy			The De Market of the Control of the
External-Actuator Cover			
Actuator Arm Lever			
Housing to Actuator Assy			
Hose Assy, Starboard			
Starboard Actuator Manifold			
Starboard Actuator Assy			
Housing-Actuator Hydraulic			VIII CAN CONTRACTOR CO
Hose Assy, Port			All the state of t
Housing - Actuator Hydraulic			
System, Port			
Port Actuator Manifold			
Port Actuator Assy			
Starboard/Port Hinge Arm			
Starboard Door Assy			
Door Seals			79.76
Door Latch Rod, Starboard Door			West of the second seco
Port Door Assy			
•			
Wiring Harness W16			
Platform, Equipped for Access			
Launcher Cylinder Hydraulic Hose Assy			
Launch Cylinder Hose Assys			
Launcher Cylinder			
Launcher Cylinder Swivel Joint			A CONTRACTOR OF THE CONTRACTOR
Elevation Cylinder Hose Assys			. Committee of the second of t
Elevation Cylinder Swivel Joint & Elbows			THE STATE OF THE S
Elevation Cylinder Assy			
Elevation Cylinder Manifold			
Elevation Cylinder			
Turnbuckle Connecting Rod			GAMES A STATE OF THE STATE OF T
Elevation Cylinder Linkage Adjustment			
Connecting Rod			
Pivot Pin			
Pivot Bearings			
Center Sheath			
Shield			
Launcher Platform Rail			
Travel Lock Assy			
Pivot Assy			
Bumper			
Stop			
Bracket, Connecting Rod			The second secon
Mercury Switch Box			
Pendulum Box Assy			
Rockets Power Distribution Box			
Rocker Arm			
Support Arm		—	W-17-1
Arm Sheath			
I MIII GIICAUI			

Pre-Induction Inspection Checklist

APPENDIX A

COMPONENT	PASS	FAIL	REMARKS:
Port/Starboard Intermediate Sheath			
Sequence Lock Manifold			
Sequence Lock Manifold Hydraulic Assys			
Support Arm Tube Assys			
Elbow			
Elbow Bracket			
Three-Hole Bulkhead			
Tube Angle Mounting			
Launcher Housing Tube Assy			
Junction Box A			
Junction Box B			
Limit Switch			NATIONAL CONTRACTOR OF THE CON
Limit Switch Arm Bracket			
Wiring Harness W15			
Latch Pivot Bracket		—	
		—	
Latch Spring		—	
Test Plugs			
Nipple			
Coupler			The part of the first of the same of the s
Lower Seal			
Sheath			
Intermediate Housing Sheath			**************************************
Port Housing Guard			
Starboard Housing Guard			
Forward Port Housing Guard			
Aft Port Housing Guard			
Forward Starboard Housing Guard			
Aft Starboard Housing Guard			
Port/Starboard Bar			
Swivel Elbow (Port H2)			
Tie-Down and Adapter Assy			
Tie-Down Adapter			
Tie-Down Assy			- 1/ 3/ 4/ (c)
Aft Wall Guard			
Aft Guard Assy			*E-14-14-14-14-14-14-14-14-14-14-14-14-14-
Aft Port Guard			11.874.0
Aft Starboard Guard			
Forward Guard Assy			
Cable Guide			
Starboard Cable Guide			
Aft Port Cable Guide			T- HAMANIAN
Lower Engine Access Cover Latch			
Upper Engine Access Cover Striker			THE STATE OF THE S
Rail			
Center Channel Assy			
Aft Pallet Rail Tie-Down Bracket			
Port/Starboard Ramp			
Rear Pallet Assy			

Pre-Induction Inspection Checklist

APPENDIX A

COMPONENT	PASS	FAIL	REMARKS:
Wear Plate			
Quick Release Pins			
Starboard Ramp Crossmember			
Ramp Wear Plates			
Aft Pallet			
Forward Pallet Assy			
Housing to Forward Pallet Hose Assys			
Capstan Hydraulic Hose Assy			
Forward Pallet Rail Tie-Down Bracket			
Quick Disconnect Coupler Fitting			
Power Distribution Box Assy			With the desiration on the second of the sec
Quick Disconnect Nipple Fitting			
200A Circuit Breaker			
2A Circuit Breaker			
10A Circuit Breaker			
200A Relay			
10A Relay			
Terminal Block			
			The state of the s
Indicator Light Assy		_	
Toggle Switch			
Slave Plug			
Capstan with Hydraulic Motor Assy			***************************************
Capstan Drum			
Reduction Gearbox			
Reduction Gearbox Lubricating Oils			
Reduction Gearbox Oil Change			
Hydraulic Filter Change			
Capstan Hydraulic Motor			
Hydraulic Power Unit			
Manual Hydraulic Pump			
Manual Hydraulic Pump Handle			
Electric Motor/Hydraulic Pump			
Electric Motor/Hydraulic Pump			
Control Manifold			
Reservoir Assy			
Sight Glass			
Relief Valve			
Pressure Gauge			
Manual Pump Outlet Tube			
Manual Pump Inlet Tube			
Clip Spring			
Hydraulic Pump Inlet Tube			
Hydraulic Pump Outlet Tube			
Wiring Harness W12		_	
Wiring Harness W12 Wiring Harness W13			
_		_	
Wiring Harness W14 Arm Switch			
Control Box			

Pre-Induction Inspection

25 August 2004

Checklist APPENDIX A

COMPONENT	PASS	FAIL	REMARKS:
Control Box & Mounting			
Brackets Assy			
Brackets			
Lamps			
Selector Knob			
Toggle Switch Guard			
Receptacles			
Receptacle Connections			
10A Relay			
Relay Connections			
Filters			
Filter Connections			1.6.180.1
System Power Switch			
System Power Switch Connections			
Panel Light			The state of the s
Panel Light Connections			
Push Switches			
Push Switch Connections			
Rotary Switch			400,000,000
Rotary Switch Connections			- 10 to Photos Ministra
Launch Angle Indicator			SPECIAL PROPERTY OF A AND COLOR OF AN COLOR OF A COLOR
Circuit Board Assy			
Circuit Board Assembly Connections			
Indicator Light			
Indicator Light Connections			
Raise/Lower Switch			**************************************
Raise/Lower Switch Connections			
Electric Wire			
Wire Connections			
Container, Top			
Container, Fop Container, Bottom			A STATE OF THE STA
Gasket, Container Joint			
Gasker, Colitainel John			The state of the s

LIST OF REPAIR PARTS AND ASSEMBLIES REQUIRED FOR REPAIRS APPENDIX B

	SPACE IS FOR COMMENTS AND OBSERVATIONS AFTER THE HAS BEEN COMPLETED. Please annotate and initial.
SPECTION	HAS BEEN COMPLETED. Please annotate and initial.
T-1	
	THE

	NAME OF THE PARTY

COMPONENT	REMARKS:
Mast Assy	
External-Actuator Cover	
Actuator Arm Lever	
Housing to Actuator Assy	
Hose Assy, Starboard	
Starboard Actuator Manifold	
Starboard Actuator Assy	
Housing-Actuator Hydraulic Hse Assy, Port	100000000000000000000000000000000000000
Housing - Actuator Hydraulic System, Port	
Port Actuator Manifold	
Port Actuator Assy	
Starboard/Port Hinge Arm	
Starboard Door Assy	
Door Seals	
Door Latch Rod, Starboard Door	
Port Door Assy	To the state of
Wiring Harness W16	74794
Platform, Equipped for Access	
Launcher Cylinder Hydraulic Hose Assy	
Launch Cylinder Hose Assys	
Launcher Cylinder	
Launcher Cylinder Swivel Joint	
Elevation Cylinder Hose Assys	APPACASA AND AND AND AND AND AND AND AND AND AN
Elevation Cylinder Swivel Joint & Elbows	
Elevation Cylinder Assy	
Elevation Cylinder Manifold	
Elevation Cylinder Elevation Cylinder	
Turnbuckle Connecting Rod	
Elevation Cylinder Linkage Adjustment	NI DELLEGICA DE LA CONTRACTOR DE LA CONT
Connecting Rod Pivot Pin	
- 1 · 0 · - 111	
Pivot Bearings	
Center Sheath	
Shield	
Launcher Platform Rail	The state of the s
Travel Lock Assy	
Pivot Assy	
Bumper	
Stop	
Bracket, Connecting Rod	
Mercury Switch Box	
Pendulum Box Assy	
Rockets Power Distribution Box	
Rocker Arm	
Support Arm	
Arm Sheath Port/Starboard	WALL TO THE STATE OF THE STATE
Intermediate Sheath	

COMPONENT	REMARKS:
Sequence Lock Manifold	
Sequence Lock Manifold Hydraulic Assy	
Support Arm Tube Assys	
Elbow	
Elbow Bracket	
Three-Hole Bulkhead Tube	
Angle Mounting	
Launcher Housing	
Tube Assys	
Junction Box A	
Junction Box B	
Limit Switch	
Limit Switch Arm Bracket	
Wiring Harness W15	
Latch Pivot Bracket	
Latch Spring	
Test Plugs	
Nipple	,
Coupler	
Lower Seal	
Sheath	
Intermediate Housing Sheath	
Port Housing Guard Starboard Housing	
Guard	
Forward Port Housing Guard	
Aft Port Housing Guard	
Forward Starboard Housing Guard	
Aft Starboard Housing Guard	
Port/Starboard Bar	
Swivel Elbow (Port H2)	
Tie-Down and Adapter Assy	
Tie-Down Adapter	,
Tie-Down Assy Aft Wall	
Guard Aft Guard Assy Aft Port Guard Aft	
Starboard Guard Forward Guard Assy Cable	
Guide Starboard Cable Guide Aft Port Cable	
Guide Lower Engine Access Cover Latch	
Upper Engine Acc Cover Strike Rail	
Center Channel Assy	
Aft Pallet Rail Tie-Down Bracket	
Port/Starboard Ramp	
Rear Pallet Assy	
Wear Plate	
Quick Release Pins	The Control of Control
Starboard Ramp Crossmember	
Ramp Wear Plates	
Aft Pallet	

COMPONENT	REMARKS:
Forward Pallet Assy	
Housing to Forward Pallet Hose Assys	
Capstan Hydraulic Hose Assys	
Forward Pallet Rail Tie-Down Bracket	
Quick Disconnect Coupler Fitting	
Power Distribution Box Assy	
Quick Disconnect Nipple Fitting 200A	
Circuit Breaker	
2A Circuit Breaker	
10A Circuit Breaker	
200A Relay	
10A Relay	
Terminal Block Indicator Light Assy	
Toggle Switch Slave Plug Capstan with	
Hydraulic Motor Assy Capstan Drum	
Reduction Gearbox	
Reduction Gearbox Lubricating Oils	
Reduction Gearbox Oil Change	
Hydraulic Filter Change	
Capstan Hydraulic Motor	
Hydraulic Power Unit	
Manual Hydraulic Pump	
Manual Hydraulic Pump Handle	
Electric Motor/Hydraulic Pump	
Electric Motor/Hydraulic Pump	
Control Manifold	
Reservoir Assy	
Sight Glass	
Relief Valve	
Pressure Gauge	
Manual Pump Outlet Tube	
Manual Pump Inlet Tube	
Clip Spring	
Hydraulic Pump Inlet Tube	
Hydraulic Pump Outlet Tube	
Wiring Harness W12	
Wiring Harness W13	
Wiring Harness W14	
Arm Switch	
Control Box	
Control Bx & Mounting Brackets Assy	
Brackets	
Lamps	
Selector Knob	- Marketing
Toggle Switch Guard	
Receptacles	THE PROPERTY OF THE PROPERTY O
Receptacle Connections	
1	

COMPONENT	REMARKS:
10A Relay	
Relay Connections	
Filters	
Filter Connections	
System Power Switch	
System Power Switch Connections	
Panel Light	
Panel Light Connections	
Push Switches	
Push Switch Connections	
Rotary Switch	
Rotary Switch Connections	
Launch Angle Indicator	
Circuit Board Assy	
Circuit Board Assy Connections	
Indicator Light	
Indicator Light Connections	
Raise/Lower Switch	
Raise/Lower Switch Connections	
Electric Wire	
Wire Connections	
Container, Top	
Container, Bottom	
Gasket, Container Joint	
•	
ADDITIONAL OBSERVATIONS:	
	The state of the s

LIST OF REPAIR PARTS AND ASSEMBLIES REQUIRED FOR REPAIRS APPENDIX C

MK154 Serial number:
ADDITIONAL COMMENTS AND OBSERVATIONS: Please annotate and initial.

LIST OF REPAIR PARTS AND ASSEMBLIES REQUIRED FOR

COMPONENT	REMARKS:
Mast Assy	
External-Actuator Cover	
Actuator Arm Lever	
Housing to Actuator Assy Hose	
Assy,Strbrd Starboard Starboard	
Actuator Manifold	
Starboard Actuator Assy	
Housing-Actuator Hydraulic Hse	
Assy, Port	
Housing – Actuator Hydraulic	
System, Port	
Port Actuator Manifold	The state of the s
Port Actuator Assy	The state of the s
Starboard/Port Hinge Arm	
Starboard Door Assy	
Door Seals	
Door Latch Rod, Starboard Door	
Port Door Assy	
Wiring Harness W16	And the second s
Platform, Equipped for Access	
Launcher Cylinder Hydraulic Hose	
Assy	
Launch Cylinder Hose Assys	
Launcher Cylinder	
Launcher Cylinder Swivel Joint	
Elevation Cylinder Hose Assys	
Elevation Cylinder Swivel Joint &	
Elbows	
Elevation Cylinder Assy	
Elevation Cylinder Manifold	
Elevation Cylinder	
Turnbuckle Connecting Rod	
Elevation Cylinder Linkage	
Adjustment	19934100
Connecting Rod	
Pivot Pin	The state of the s
Pivot Bearings	
Center Sheath	
Shield	
Launcher Platform Rail	The second secon
Travel Lock Assy	
Pivot Assy	
Bumper	1000
Stop	
Bracket, Connecting Rod	Fall Control of the C
Mercury Switch Box Pendulum Box	
Assy Rockets Power Distribution Box	
Rockets Fower Distribution Box	

LIST OF REPAIR PARTS AND ASSEMBLIES REQUIRED FOR

COMPONENT	REMARKS:
Rocker Arm Support Arm Arm	Market Ma
Sheath Port/Starboard Intermediate	
Sheath	
Sequence Lock Manifold	
Sequence Lck Manifold Hydraul Asy	
Support Arm Tube Assys	
Elbow	
Elbow Bracket Three-Hole Bulkhead	
Tube Angle Mounting	
Launcher Housing Tube Assys	
Junction Box A	
Junction Box B	
Limit Switch	
Limit Switch Arm Bracket Wiring	
Harness W15	
Latch Pivot Bracket	
Latch Spring	
Test Plugs	
Nipple	
Coupler	
Lower Seal	
Sheath	
Intermediate Housing Sheath	
Port Housing Guard Starboard	
Housing Guard	
Forward Port Housing Guard	
Aft Port Housing Guard	
Forward Starboard Housing Guard	
Aft Starboard Housing Guard	NAME OF THE PROPERTY OF THE PR
Port/Starboard Bar	WEB-TENNIA (1971 AND 1971 AND
Swivel Elbow (Port H2)	
Tie-Down and Adapter Assy	
Tie-Down Adapter	
Tie-Down Assy Aft Wall Guard Aft	
Guard Assy Aft Port Guard Aft	
Starboard Guard Forward Guard Assy	
Cable Guide Starboard Cable Guide	
Aft Port Cable Guide Lower Engine	
Access Cover Latch Upper Eng	1970 - 197
Access Cover Striker Rail	
Center Channel Assy	
Aft Pallet Rail Tie-Down Bracket	
Port/Starboard Ramp	
Rear Pallet Assy	
Wear Plate	
Quick Release Pins	
Starboard Ramp Crossmember	
Ramp Wear Plates	

25 August 2004

LIST OF REPAIR PARTS AND ASSEMBLIES REQUIRED FOR

COMPONENT	REMARKS:
Aft Pallet	
Forward Pallet Assy	
Housing to Forward Pallet Hose Assy	
Capstan Hydraulic Hose Assys	
Forward Pallet Rail Tie-Down	
Bracket	
Quick Disconnect Coupler Fitting	
Power Distribution Box Assy	
Quick Disconnect Nipple Fitting	
200A Circuit Breaker	
2A Circuit Breaker	
10A Circuit Breaker	
200A Relay	
10A Relay	
Terminal Block Indicator Light Assy	
Toggle Switch Slave Plug Capstan	
with Hydraulic Motor Assy Capstan	
Drum Reduction Gearbox	
Reduction Gearbox Lubricating Oils	
Reduction Gearbox Oil Change	
Hydraulic Filter Change	
Capstan Hydraulic Motor	
Hydraulic Power Unit	
Manual Hydraulic Pump	· · · · · · · · · · · · · · · · · · ·
Manual Hydraulic Pump Handle	
Electric Motor/Hydraulic Pump	
Electric Motor/Hydraulic Pump	
Control Manifold	
Reservoir Assy	
Sight Glass	
Relief Valve	
Pressure Gauge	
Manual Pump Outlet Tube	
Manual Pump Inlet Tube	
Clip Spring	
Hydraulic Pump Inlet Tube	
Hydraulic Pump Outlet Tube	The state of the s
Wiring Harness W12	We will be a second of the sec
Wiring Harness W13	· · · · · · · · · · · · · · · · · · ·
Wiring Harness W14	
Arm Switch	
Control Box	
Contrl Bx & Mounting Brackets Assy	
Brackets	
Lamps	unit.
Selector Knob	
Toggle Switch Guard	
Receptacles	

25 August 2004

LIST OF REPAIR PARTS AND ASSEMBLIES REQUIRED FOR

COMPONENT	REMARKS:
Receptacle Connections	
10A Relay	
Relay Connections	
Filters	
Filter Connections	
System Power Switch	
System Power Switch Connections	
Panel Light	
Panel Light Connections	
Push Switches	
Push Switch Connections	
Rotary Switch	
Rotary Switch Connections	
Launch Angle Indicator	
Circuit Board Assy	
Circuit Board Assy Connections	
Indicator Light	
Indicator Light Connections	
Raise/Lower Switch	
Raise/Lower Switch Connections	
Electric Wire	,
Wire Connections	
Container, Top	
Container, Bottom	
Gasket, Container Joint	
,	
ADDITIONAL NOTES:	
	AND THE RESIDENCE OF THE PROPERTY OF THE PROPE
	TOTAL CONTRACTOR OF THE CONTRA
100	
A CONTRACTOR OF THE CONTRACTOR	
	300 F 5 40 F 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5

CONTRACT DATA REQUIREMENTS LIST

(1 Data Item)

Form Approved OMB No. 0704-01B8

The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Sand comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquerters Services, Directorate for Information Deparations and Reports (0701-0188), 1215 Jafferson Davis Highway, Suite 1204, Artington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to collection of information if it does not display a currently valid DMB control number. Please DD NDT RETURN your form to the above address. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.

A. CONTRACT LINE I	CONTRACT LINE ITEM NO. B. EXHIBIT C. CATEGORY: TDP TM OTHER								
D. SYSTEM/ITEM Mine Cleara	EM/ITEM ne Clearance Launcher, MK154			F. CONTRA					
					3. SUBTITLE				
A001	Red	quest For	Deviation (R)	FD)		Configuration Management			
4. AUTHORITY (Data Acquisi	tion Document No.) CMAN-80640C		5. CONTRACT REFEREN	OW Para 3.3		Marine Corps Logistics Comman Albany (MCLCA) (Code 566)			and,
7. DD 250 REQ	9. DIST STATEMENT REQUIRED	10. FREQUENC	Y	12. DATE OF FIRST SUBMISSION		14. DISTRIBUTION			
LT 8. APP CDDE	neadiles	SEE	E BLK 16	SEE BLK	16	a. Addressee	b. COPIES Final		
N/A	A		N/A	SUBMISSION N/A		8. ADDRESSEE	Draft		Repro
16. REMARKS						MCLCA (566-1)	0	1	0
format.				omitted in .doc or	_				
Blks 10 & 12 - RFDs shall be submitted to obtain authorization to deliver nonconforming material which does not meet prescribed configuration documentation.				Г					
RFDs will be receipt by the C	eviewed and disposorement.	osition de	etermined with	in 20 working da	ys upon				
RFDs submiiss mbmatcomconf	ion/notification sh figmngmnt@logco	nall be se om.usmc	nt to: .mil						
Distribution Sta	atement A: Appre	oved for	public release	, distribution is ur	ılimited.				
									-
						15. TOTAL	0	1	0
G. PREPARED BY	1		H. DATE	I. APPROVED BY		12.11	J. DATI		
Cohs	1 father		8-9-0	4 MM	Ma	Murs	171	tuzio	ery
DD FORM 1423-1	AUG 96 (FG)			VIOUS EDITION MAY BE I	ISED		Рапе		Dagge

17. PRICE GROUP

18. ESTIMATED

TOTAL PRICE